

Safety Data Sheet

Issue Date: 19-Sep-2007

Revision Date: 01-Jan-2024

Version 1

1. IDENTIFICATION

Product Identifier Product Name	T-100 PRIMER
Other means of identification SDS #	TD-011-OSHA
UN/ID No	UN1263
Recommended use of the chemica	
Recommended Use	Plating.
Details of the supplier of the safety Supplier Address Tolber Chemical Division 220 West 5th Street Hope, AR 71801	<u>data sheet</u>
Emergency Telephone Number Company Phone Number Emergency Telephone (24 hr)	870-777-3251 INFOTRAC 1-352-323-3500 (International) 1-800-535-5053 (North America)
	2. HAZARDS IDENTIFICATION
Appearance Clear liquid	Physical State Liquid
Classification	

Odor Ketone

CI

Serious eye damage/eye irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
Flammable Liquids	Category 2

Hazards Not Otherwise Classified (HNOC)

May be harmful if swallowed

<u>Signal Word</u> Danger

Hazard Statements

Causes serious eye irritation May cause respiratory irritation. May cause drowsiness or dizziness Highly flammable liquid and vapor



Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling Avoid breathing dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area Keep away from heat/sparks/open flames/hot surfaces. — No smoking Keep container tightly closed Ground/bond container and receiving equipment Use explosion-proof equipment Use only non-sparking tools Take precautionary measures against static discharge Wear protective gloves/protective clothing/eye protection/face protection Keep cool

Precautionary Statements - Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing Call a poison center or doctor/physician if you feel unwell IN CASE OF FIRE: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Unknown Acute Toxicity

80% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Methyl ethyl ketone	78-93-3	15-25

If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. FIRST-AID MEASURES

First Aid Measures

Eye Contact	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Skin Contact	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.
Ingestion	Do not induce vomiting. Call a physician or poison control center immediately.
Most important symptom	is and effects
Symptoms	Vapors may irritate eye; Liquid and mist may severely irritate or damage the eye. Skin contact may result in irritation, defatting or dermatitis. Repeated exposure may cause skin dryness or cracking. Inhalation may cause drowsiness or dizziness. Headache. Fatigue and weakness. Ingestion may cause irritation, nausea, vomiting.

Indication of any immediate medical attention and special treatment needed

Notes to Physician

Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Dry chemical. Carbon dioxide (CO2). Foam.

Unsuitable Extinguishing Media Not determined.

Specific Hazards Arising from the Chemical

Highly flammable liquid and vapor.

Hazardous Combustion Products Carbon oxides. Combustion may release noxious or toxic vapors.

Sensitivity to Static Discharge Take precautionary measures against static discharge.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions	Use personal protective equipment as required.	
For Emergency Responders	Use personal protection recommended in Section 8. Remove all sources of ignition.	
Environmental Precautions	See Section 12 for additional Ecological Information. See Section 13: DISPOSAL CONSIDERATIONS.	
Methods and material for containment and cleaning up		

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Clean-Up	Absorb spillage with non-combustible, absorbent material. Dispose of all contaminated
	trash in accordance with local regulations.

Ketone

Not determined

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling	Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Ground/bond container and receiving equipment. Use explosion proof equipment. Use only non-sparking tools. Take precautionary measures against static discharges. Wear protective gloves/protective clothing and eye/face protection. Wash face, hands and any exposed skin thoroughly after handling. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area.	
Conditions for safe storage, including any incompatibilities		
Storage Conditions	Store locked up. Keep containers tightly closed in a dry, cool and well-ventilated place.	

Incompatible Materials Strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Methyl ethyl ketone	STEL: 300 ppm	TWA: 200 ppm	IDLH: 3000 ppm
78-93-3	TWA: 200 ppm	TWA: 590 mg/m ³	TWA: 200 ppm
		(vacated) TWA: 200 ppm	TWA: 590 mg/m ³
		(vacated) TWA: 590 mg/m ³	STEL: 300 ppm
		(vacated) STEL: 300 ppm	STEL: 885 mg/m ³
		(vacated) STEL: 885 mg/m ³	-

Appropriate engineering controls

Engineering Controls	Apply technical measures to comply with the occupational exposure limits.		
Individual protection measures, such as personal protective equipment			
Eye/Face Protection	Splash proof chemical safety goggles.		
Skin and Body Protection	Chemical resistant, impermeable gloves. Suitable protective clothing. Long sleeve shirt and long pants. Protective shoes or boots.		
Respiratory Protection	In case of inadequate ventilation wear respiratory protection.		
General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Wash hands with soap and water before handling food.			

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State Appearance Color	Liquid Clear liquid Clear	Odor Odor Threshold
<u>Property</u> pH Melting Point/Freezing Point	<u>Values</u> Not determined Not determined	Remarks • Method
Boiling Point/Boiling Range Flash Point Evaporation Rate Flammability (Solid, Gas)	93 °C / 200 °F -5 °C / 23 °F 3.0 Liquid-Not applicable	Tag Closed Cup

Upper Flammability Limits	12%
Lower Flammability Limit	2%
Vapor Pressure	Not determined
Vapor Density	1.0
Specific Gravity	0.85
Water Solubility	Insoluble in water
Solubility in other solvents	Not determined
Partition Coefficient	Not determined
Auto-ignition Temperature	Not determined
Decomposition Temperature	Not determined
Kinematic Viscosity	Not determined
Dynamic Viscosity	Not determined
Explosive Properties	Not determined
Oxidizing Properties	Not determined

(Air=1) (1=Water)

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to Avoid

Avoid contact. Keep away from heat, sparks and open flame.

Incompatible Materials

Strong oxidizing agents.

Hazardous Decomposition Products

Thermal decomposition may produce oxides of carbon.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information	
Eye Contact	Causes serious eye irritation. May cause eye damage if direct contact occurs.
Skin Contact	Avoid contact with skin. Repeated exposure may cause skin drynessor cracking.
Inhalation	Avoid breathing vapors or mists.
Ingestion	Do not taste or swallow. Ingestion can cause irritation, nausea, or stomach distress.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Methyl ethyl ketone	= 2737 mg/kg (Rat)	= 6480 mg/kg (Rabbit)	-
78-93-3			

Information on physical, chemical and toxicological effects

Symptoms

Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Carcinogenicity	This product does not contain any carcinogens or potential carcinogens as listed by OSHA, IARC or NTP.
STOT - single exposure	May cause respiratory irritation. May cause drowsiness or dizziness.
Numerical measures of toxicity	

Not determined

12. ECOLOGICAL INFORMATION

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Component Information

Chemical Name	Algae/aquatic plants	Fish	Toxicity to	Crustacea
			microorganisms	
Methyl ethyl ketone		3130 - 3320: 96 h	EC50 = 3403 mg/L 30 min	520: 48 h Daphnia magna
78-93-3		Pimephales promelas mg/L	EC50 = 3426 mg/L 5 min	mg/L EC50 5091: 48 h
		LC50 flow-through		Daphnia magna mg/L EC50
		_		4025 - 6440: 48 h Daphnia
				magna mg/L EC50 Static

Persistence/Degradability

Not determined.

Bioaccumulation

Not determined.

Mobility

Chemical Name	Partition Coefficient
Methyl ethyl ketone	0.29
78-93-3	

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Wastes	Disposal should be in accordance with applicable regional, national and local laws and regulations.
Contaminated Packaging	Disposal should be in accordance with applicable regional, national and local laws and regulations.

US EPA Waste Number

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Methyl ethyl ketone	U159	Included in waste streams:	200.0 mg/L regulatory level	U159
78-93-3		F005, F039		

<u>California Hazardous Waste Status</u> This product contains one or more substances that are listed with the State of California as a hazardous waste

Chemical Name	California Hazardous Waste Status
Methyl ethyl ketone	Toxic
78-93-3	Ignitable

14. TRANSPORT INFORMATION

<u>Note</u>

Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

DOT

UN/ID No	UN1263
Proper Shipping Name	Paint
Hazard Class	3
Packing Group	II
IATA UN/ID No	UN1263

	011203
Proper Shipping Name	Paint
Hazard Class	3
Packing Group	II
IMDG	
UN/ID No	UN1263

MDG	
UN/ID No	UN126
Proper Shipping Name	Paint
Hazard Class	3
Packing Group	П

15. REGULATORY INFORMATION

International Inventories

Not determined

US Federal Regulations

CERCLA

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Methyl ethyl ketone	5000 lb		RQ 5000 lb final RQ
78-93-3			RQ 2270 kg final RQ

<u>SARA 313</u>

Not determined

US State Regulations

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Methyl ethyl ketone	Х	Х	Х
78-93-3			

16. OTHER INFORMATION

NFPA HMIS	Health Hazards Not determined Health Hazards Not determined	Flammability Not determined Flammability Not determined	Instability Not determined Physical Hazards Not determined	Special Hazards Not determined Personal Protection Not determined
Issue Date: Revision Date: Revision Note:	19-Sep-2007 01-Jan-2024 New format			

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet